N5751A-08

Safety Service Note

Implemented During Normal Course of Providing Support

Supersedes: NONE

N5751A DC System Power Supply, 300V, 2.5A, 750W

Serial Numbers: US25D4679B to US27M5171L, US08B2403L to US15J9871P

POSSIBLE "SHOCK" HAZARD

WARNING

HAZARD CLASS #2

The Problem – Regulatory noncompliance with the option 901 (Power cord for Australia / New Zealand)

Parts Required:

P/N Description Qty.

8120-4419

ADMINISTRATIVE INFORMATION

ACTION	[X] ON SPECIFIED FAILURE	STANDARDS	
CATEGORY:	[[]] AGREEABLE TIME	LABOR: 0.1 Hours	
LOCATION CATEGORY:	[X] CUSTOMER INSTALLABLE []] ON-SITE (active On-site contract required) [X] SERVICE CENTER []] CHANNEL PARTNERS	SERVICE: [[]] RETURN INVENTORY: [X] SCRAP [[]] SEE TEXT	USED [[]] RETURN PARTS: [X] SCRAP [[]] SEE TEXT
AVAILABILITY: ALWAYS		NO CHARGE AVAILABLE UNTIL	: EOS
	[[]] Calibration Required [X] Calibration NOT Required	PRODUCT LINE: SP AUTHOR: SJ	

ADDITIONAL INFORMATION:



Situation:

The Australian/New Zealand Regulations requires the use of power cord sets that meet AS3112. Since 2005, the live and neutral pins must be insulated for a prescribed length of pin. It was found that Keysight Technologies had shipped some power cord sets with the older style plug. To address this non-compliance, Keysight Technologies will supply a new power cord (part number 8120-4419) to affected customers.

Solution/Action:

- 1. Verify that your instrument(s) corresponds to the above model and serial numbers.
- 2. Replace the original power cord with the new power cord supplied by Keysight Technologies.
- 3. Destroy the original power cord to prevent it from being used with any electrical equipment, and recycle responsibly.

Revision History:

Date	Service Note Revision	Author	Reason for Change	
07 June 2016	01	SJ	As Published	